

Tech Specs

The product features and specifications are subject to change without prior notice

If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could break and cause the projector to drop from the ceiling.

If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance.

Technology

Projection System

3LCD Technology, RGB liquid crystal shutter

LCD Panel

0.59 inch with MLA (D10)

Image

Color Light Output

3,000 Lumen- 2,000 Lumen (economy) In accordance with ISO 21118:2020

White Light Output

3,000 Lumen - 2,000 Lumen (economy) In accordance with ISO 21118:2020

Resolution

WXGA

High Definition

HD ready

Aspect Ratio

16:10

Light source

Lamp

Lamp

UHE, 188 W, 6,000 h durability, 12,000 h durability (economy mode)

Keystone Correction

Manual vertical: $\pm 30^\circ$, Manual horizontal $\pm 30^\circ$

Colour Video Processing

8 Bits

2D Vertical Refresh Rate

100 Hz - 120 Hz

Colour Reproduction

16.77 million colours

Optical

Throw Ratio

1.27 - 1.71:1

Zoom

Digital, Factor: 1 - 1.35

Lens

Optical

Screen Size

25 inches - 378 inches

Projection Distance Wide

0.9 m - 10.4 m

Projection Distance Tele

0.9 m - 10.4 m

Projection Distance Wide/Tele

1.64 m (60 inch screen

Projection Lens F Number

1.44

Projection Lens Focus

Manual

Offset

7 : 1

Connectivity

Interfaces

HDMI 1.4, USB 2.0-A, USB 2.0 Type B (Service Only)

Epson iProjection App

n/a

Advanced Features

Security

Kensington lock, Padlock, Security cable hole

2D Colour Modes

Dynamic, Cinema, Presentation, sRGB, Blackboard, Vivid

Other features

A/V mute, Built-in speaker, Horizontal and vertical keystone correction, MHL audio/video interface, Quick Corner

Video Color Modes

Blackboard, Cinema, Dynamic, Presentation

General

Power consumption

270 Watt, 214 Watt (economy), 0.5 Watt (standby)

Supply Voltage

AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions

295 x 211 x 87 mm (Width x Depth x Height)

Product weight

2.4 kg

Noise Level

Normal: 38 dB (A) - Economy: 29 dB (A)

Supported Temperature

Operation 5° C - 40° C

Supported Humidity

Operation -10% - 60%, Storage 10% - 90%

If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material

degradation which over time could break and cause the projector to drop from the ceiling.

If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance.

Loudspeaker

5 Watt

What's in the box

Main unit, Power cable, Quick Start Guide, Remote control incl. batteries, User manual (CD), Warranty card

Room Type / Application

Home Office, Home Photo, Streaming, TV & Box sets

Positioning

Desktop

Colour

White / Black
