

# XM4000HS/G

## Warranty

100% Credit: 0/1400

## Technical specification

Power (W) - 4000  
Rated Current (A.D.C.) - 135  
Voltage (V.D.C.) - 30  
Current Control Range (A.D.C.) - 80-150  
Average Lumen Output (Lm) - 155000  
Burning Position -  $H\pm 20^\circ V\pm 20^\circ$   
Forced Air Cooling (m/sec.) - 10-13  
Anode (+) Base  $\emptyset$  - Pin  $\emptyset$  or Thread (mm) - 30-9.5  
Cathode (-) Base  $\emptyset$  - Pin  $\emptyset$  or Thread (mm) - 30-7.9

## Cross Reference

OSRAM - XBO 4000W/HS OFR  
Christie - CXL-40SC  
USHIO - UXL-40SC  
Superior Quartz - SX42001

## Projector Reference

NEC NC2500S  
NEC NC3200S  
NEC NC3240S 4kW  
NEC NC3240S 7kW  
L.P. ASSOCIATES 4KW Sky Dancer  
L.P. ASSOCIATES 4KW XELAMP Architectural Spotlight  
LYCIAN STAGE LIGHTING Lycian 1294 SuperArc 4K  
PHOEBUS MANUFACTURING Silverbeam PSL-20 4K Xenon  
PHOEBUS MANUFACTURING Silverbeam 360 4KW  
SPACE CANNON ILLUMINATION 4.0kW  
STRONG INTERNATIONAL Gladiator IV